## PAGE 1 OF 2 CITY OF ALBUQUERQUE RFB2006-147-SB MEDIUM-DUTY TRACTOR MESA TRACTOR

AGENCY:				
DEPARTMENT:				
DIVISION:				
REQUISITION #:			PO #:	
DESCRI	PTION:	Medium-Duty Tractor	MAKE:	Kubota
VENDOR:		Mesa Tractor	MODEL:	L3830HST
BASE COST PER UNIT:		\$ 16,489.97	ENGINE:	Kubota D1803

## Standard Specifications

1.	Engine							
	1.1. Type:	E-TVCS, indirect injection, vertical, liquid-cooled, 4-cycle diesel						
	1.2. Engine Gross Power:	39.0 HP						
	1.3. Engine Net Power	37.4 HP						
	1.4. PTO Power:	30.5 HP						
	1.5. Number of Cylinders:	3						
	1.6. Bore & Stroke:	3.4 inches x 4.0 inches						
	1.7. Total displace:	111.5 cubic inches						
	1.8. Rated speed:	2,700 RPM						
	1.9. Battery:	80D 26R, 12V						
	1.10. Alternator:	12V, 40A						
	1.11. Fuel tank capacity: 10.6 US gallons							
2.	PTO							
	2.1. Rear PTO							
2.1.1. Revolution: 1 speed: 540 RPM								
	2.1.2. Type: Independent with master clutch							
	2.2. Mid PTO:	Mid PTO at 2,000 RPM						
3.	Hydraulic:							
	3.1. Lift control type: Manufacturer's standard.							
	3.2. Implement pump:	8.3 GPM						
	3.3. Power steering pump:	4.9 GPM						
	3.4. Total hydraulic flow:	13.2 GPM						
	3.5. 3-point hitch:	Category 1						
	3.6. Lift capacity at 24 inch	es behind lift point: 2,760 pounds						
4.	Traveling System							
	4.1. Transmission	Hydrostatic four-wheel drive						
	Hydrostatic power steering							
	4.3. Brake:	Wet disc type						
	4.4. Clutch:	Dry type single stage						
5.	Standard tire size							
	5.1. Front: 8.3 – 16							
	5.2. Rear: 14.9 – 24							
6.	Travel Speeds							
	6.1. No. of speeds at rated engine speed: 3 ranges forward and 3 ranges reverse							

## PAGE 2 OF 2 CITY OF ALBUQUERQUE RFB2006-147-SB MEDIUM-DUTY TRACTOR MESA TRACTOR

7.	Dimensions											
	7.1. Overall length (without 3P):			117.5 inches								
	7.2. Overall wid	lth (minimu	ım tread):	66.5 inches								
	7.3. Overall hei	ght (with R	OPS):	91.1 inches / 84.8 inches								
	7.4. Wheelbase	<b>)</b> :		72.4 inches								
	7.5. Minimum ground clearance:			14.8 inches								
	7.6. Front and Rear Tread:			Manufacturer's standard. Front and rear tread shall be compatible.								
8.	Minimum turning radius 9.5 feet											
9.	Weight (with ROPS) 3,340 pour			ounds								
	OPTIONS											
	DESCRIPTION				MODEL	PRICE (quantity 1 ea.)						
		Max. Lift	Height:	102.4 inches (pivot pin)								
		Lift Capacity:		1,870 lbs. (pivot pin)	LA723							
A.	Loader Bucket:	Breakout Force:		2,605 lbs. (500 mm forward)		\$	3,708.03					
		Raising Time:		3.3 seconds (to full height without load)								
		Lowering	g Time:	2.2 seconds (without load)								